MPRI COMPLB
Part II
Query complexity

Frame 1

Query Complexity


Decision tree

Boolean function $f : \{0,1\}^n \to \{0,1\}$

f least significant digit of x codes for $f(x)$

Goal: find the value of input x at minimal cost in queries





The computation must be query based: to every input x leading to the same leaf $f(x)=b$

for $f(x_0) = f(x_1) = b$

Relevant analogue in nondeterministic case: right.



Frame 2

Frame 3



K_n — complete graph with n vertices

n vertex $\leftrightarrow$ edge in decision tree

edges whose endvertices are found $\leftrightarrow$ to be

Def A decision tree for Boolean function $f : \{0,1\}^n \to \{0,1\}$ is a tree labelled with indices $i \in [n]$ by queries x_i of the queries made on x to determine the value of $f(x)$ leaving

Frame 4

Frame 5

We write $T(x)$ for the value of the decision tree on x.

The **cost** of deciding on x with T

$\mathrm{cost}(T,x)$ = depth of the leaf obtained by on T

The **cost of** T $\mathrm{Cost}(T) = \max_{x \in \{0,1\}^n} \mathrm{cost}(T,x)$

Def Query complexity: $D(f)$ = decision tree complexity of f

$D(f) = \min_{T \text{ decision tree for } f} \mathrm{cost}(T)$

Def $R(f)$: randomized decision tree complexity:

$T = \{T_x\}$ probability for of picking tree T_x

Compute value by T_x

- Cost $(T_x, x) =$ worst cost (T_x, x)
- Correctness $\forall x \; \mathbb{P}_{T_x}(T_x(x) = f(x)) \geq \frac{2}{3}$

$R(f) = \min_{T \text{ simple enough}} \max_{x \in \{0,1\}^n} \mathrm{cost}(T,x)$

Frame 6

Example:

$OR_n(x) = \begin{cases} 1 & \text{if } \exists i \;\; x_i = 1 \\ 0 & \text{else} \end{cases}$

Easy to see that

$D(OR_n) = n$

$AND_n(x) = \begin{cases} 1 & \text{if } \forall i \;\; x_i = 1 \\ 0 & \text{else} \end{cases}$

Frame 7

$R(f) = \min_{T \text{ simple enough}} \max_{x \in \{0,1\}^n} \mathrm{cost}(T,x)$

$\mathrm{cost}(C) = \max_{\text{inputs}} \mathrm{cost}(T,x)$

Obs $D(f) \leq n$

$R(f) \leq n$

$R(f) \leq D(f)$

Def $R_2(f)$ same more randomized BT for this model the cost is the expectation

$\mathrm{cost}(T,x) = \text{number of coins flipped by } T \text{ on } x$

$\mathrm{cost}(T) = \max_{x \in \{0,1\}^n} \mathbb{E}_T \, \mathrm{cost}(T,x)$

Def $R(f) \geq R_2(f) \geq D(f) \quad \forall f$

Proof: obvious, given a BT T for f with error $\leq \frac{1}{3}$ (Markov inequality) there is a deterministic tree with cost $\leq 3 \cdot$ (Markov inequality) $\leq \frac{1}{2}$

Frame 8

THEOREM function:

Alternating (informal)

Give a decision tree for THEOREM

$MAJ_n = \begin{cases} 1 & \text{if } \sum x_i \geq \frac{n}{2} \\ 0 & \text{else} \end{cases}$

$PARITY_n = \begin{cases} 1 & \text{if } \sum x_i = 1 \pmod 2 \\ 0 & \text{else} \end{cases}$

Frame 9

Ex OR_2

$D(OR_2) \leq 2 = n$

$R(OR_2) \leq 1.5 = n$ (using only 0's in leaving cost 1 tuples)

$R(OR_n) \leq n$?

Is $R(OR_n) = \frac{3n}{4}$?

$\leq$: look at $\frac{n}{4}$ of the bits (at random)

$\geq$: Yao Davis's Lemma see Lecture 5

$E[\#$ bits $] \geq \frac{3n}{4}$

Idea: if we look at $\frac{n}{4}$ bits then there are still many cases with both 0 and 1 in their bits, and then input is one of 0^n or $0^{n-1}1$ which flipped a 0.


Frame 10


Question using randomness

Consider the circuit

Assume Active input strongly going parts:

(a) 

(b) 

C 

Computer a function f with error $\leq \frac{1}{3}$ if $\forall x \; \mathrm{Pr}[\text{output bit} = f(x)] \geq \frac{2}{3}$

$\mathrm{Cost}(C) = k$ # of query operations

$Q(f) = \min_{C \text{ correct for } f} \mathrm{cost}(C)$

Thm $Q(OR_n) = \Theta(\sqrt{n}) \ll R(OR_n)$

Lower bound : Grover's adv (1996)

Frame 11

Certificate complexity

Objective: define $C(f)$ that is a lower bound for $D(f)$ i.e. $C(f) \leq D(f)$

Giving a lower bound on D : suffice to compute $C(f)$

Def A partial assignment $s \subseteq \{0,1\}^n$ is consistent with f if $\exists x \in \{0,1\}^n$ and f is a total function such that $s \subseteq x$

Ex $f : 4 \, x_3 \, x_2 \, x_1 \, x_0 \to x$

$x \cap s$: 000 $\subseteq$ 1 0 0 1

Given a decision tree T and an input x we will associate three partial assignment s' corresponding to the queries made on input x

Def s' is a CERTIFICATE for f if $\exists x \in \{0,1\}^n \; s' \subseteq x$ and $f(x) = b \quad \forall x \cap s'$

Frame 12

Example OR_n

$x = 0 0 1 0 0 1$

$s' = x \; x \; 1 \; x \; x \; x$

$C(OR_n) = n$

because 0^n requires $s' = 0 \ldots 0$

Alternate

① $C(TH_{n,k}) = ?$

$TH_{n,k} = \begin{cases} 1 & \text{if } \sum x_i \geq k \\ 0 & \text{else} \end{cases}$

② $C(TH_{n,k}) = ?$

③ $\text{TRIBES}_n = AND_{\sqrt{n}} \circ OR_{\sqrt{n}}$

$C(\text{TRIBES}_n) = ?$

Frame 13

Def For a partial assignment s its size $|s| = |\{i : \exists b \in \{0,1\}, s_i = b\}|$

Def $C(f,x) = \min\{|s| : x \cap s$ and f is a constant for $f\}$

$C(f) = \max_x C(f,x)$

Def $C_0(f) = \max_{x \in f^{-1}(0)} C(f,x)$

$C_1(f) = \max_{x \in f^{-1}(1)} C(f,x)$

Ex $C_0(OR_n) = n$

$C_1(OR_n) = ?$ 1

Thm $C(f) \leq D(f)$

Frame 14

Thm $\forall f \; C(f) \leq C_0(f) \cdot C_1(f)$

Recursive argument

Proof Let $S_0 \subseteq \{0,1\}^n$ be a set of 0-certificates for f

$S_1 \subseteq \{0,1\}^n$ be a set of 1-certificates

$B_0 = \{x \in \{0,1\}^n : \exists s \in S_0 \; s \subseteq x\}$

$B_1 = \{x \in \{0,1\}^n : \exists s \in S_1 \; s \subseteq x\}$

$B_0 \cap B_1 = \emptyset$ impossible

Step f_0 and f_1 must be disjoint (at) otherwise $\exists x \in B_0 \cap B_1$ and $f(x) = 0$ and $f(x) = 1$ impossible

Ex $f_0 : x \; x \; x \; 1 \; x \; x \; x \; 1$ $\quad$ $f_0(x) = 0$

$f_1 : x \; x \; 1 \; x \; x \; x \; 1 \; x$ $\quad$ $f_1(x) = 1$

$S_1 = \{x_2 = 1, x_6 = 1\}$ and $x_2 = 1$

Conclusion: $\forall x \in \{0,1\}^n \; f(x) = b \Rightarrow x \in B_b$ and $f(x) \neq b \Rightarrow x \notin B_b$

Frame 15

Def Given $S_b \subseteq$ set of b-certificates for f

S_b ——— 1

Decision tree for f on input x

Trick : certificate $S \in S_b$

Idea: query to ask the value of i, i_0 if thing $= s_i$ agree with S

— output b ...

Otherwise

Restrict f to $f|_{x_i = 1 - s_i}$ (opposite of s_i)

If S is consistent with $f|_{x_i = 1 - s_i}$ then f is constant on S (otherwise x would be a counterexample) and S_b should have been chosen, (all consistent with x)

$S_b' = S_b \setminus \{S\}$

Each iteration makes $\leq C_1(f)$ queries

iterations $\leq |S_b(f)|$ since S certificate was removed in S_b'

Stop by $\neq S$ at each step

Frame 16

For next time

What about non-total functions?

- Check that they terminate
- property does not hold for the following

$GTH(x) = \begin{cases} 1 & \text{if } \exists k \text{ of } x_i = 1 \\ 0 & \text{if } \exists n-k+1 \text{ of } x_i = 0 \\ \text{not } \{0,1\} & \text{if neither} \end{cases}$

